

To accompany plans dated \_

Post Type	Anchor Bolts				Square Pedestal						CIDH Pile						
	Total	Dia (mm)	BC (mm)	Total Length (mm)	Pedestal Square one side (mm)	Reinforcing			Ноор		Pile	Pile	Reinforcing			Spiral	
						Total	Bar Size	Spacing each face	Bar Size	Pitch	Dia (mm)	Depth (m) **	Total	Bar Size	BC (mm)	Bar Size	Pitch
I-S	12	51	711	1270	1600	16	32	346	16	89	1372	5.5	26	32	1143	16	89
∐-S	12	51	711	1270	1600	16	32	346	16	89	1372	6.0	26	32	1143	16	89
∭-S	12	51	787	1270	1600	16	32	346	16	89	1372	7.0	26	32	1143	16	89
I <b>∑</b> -S	14	51	864	1270	1600	16	32	346	16	89	1372	7.0	26	32	1143	16	89
<b>∑</b> -S	16	64	965	1524	1763	16	36	381	16	89	1524	8.0	28	36	1295	16	89
<b>∑I-</b> S	16	64	1041	1524	1763	16	36	381	16	89	1524	8.5	28	36	1295	16	89
VII-S	16	64	1041	1524	1763	16	36	381	16	89	1524	8.5	28	36	1295	16	89

\* \* Use Foundation Depth shown in table unless otherwise shown on the Project Plans.

## **NOTES**

- 1. For anchor bolt layout see post sheet.
- 2. For "Base P elevation" see Project Plans.
- 3. Longer side of post shall be normal to axis of sign.
- 4. Prior to erection of the post, backfill which is epuivalent to the surrounding material, shall be in place.
- 5. Pedestal shall be formed 150 mm Min below ground surface. Remainder to be placed against undisturbed material.
- 6. Slope protection required when indicated on the Project Plans.
- 7. Foundation design is based on 2001 AASHTO article 13.6 Broms' approximate procedure assuming a cohesionless material. The angle of internal friction used is 30° and unit weight of soil used is 1922 kg/m³.

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION

## OVERHEAD SIGNS-TRUSS TWO POST TYPE SQUARE PEDESTAL PILE FOUNDATION

NO SCALE

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN

NSP S13C, NSP S13A, NSP S13B AND NSP S13D DATED DECEMBER 30, 2004 SUPERSEDE RSP S13 DATED OCTOBER 26, 2000 AND STANDARD PLAN S13 DATED JULY 1, 1999-PAGE 232 OF THE STANDARD PLANS BOOK DATED JULY 1999.

NEW STANDARD PLAN NSP \$13C

□□-S □□-S □□-S □□-S □□-S □□-S □□-S □□-S	16         64         965           16         64         1041           16         64         1041
on New Std Plans NSP S3A and see NSP S3B    On New Std Plans NSP S3A and see NSP S3B	* * Use Foundati otherwise sh
Pedestal vertical reinforcement, see table for size  Place concrete against undisturbed material	
Permissible Const joint  Vert Reinf	
Ground away f  75 CIr Pile diameter See table  See table	d surface from traffic otection 6
Vertical reinforcement equally spaced (See table)  Section A-A  Cround surface adjacent to traffic  Parallel C  Section A-A  DETAIL C	155 Max 25 Min

Pedestal Vert Reinf

Total 16, see table

Spiral reinforcement

Axis of sign

100 Max mortar

to traffic

-25 Min 155 Max

Ground surface adjacent

for size

-Base ₧ Elev

#16 @ 89

SECTION B-B

Vertical reinforcement

Ground surface

Embed 1016 mm for 51 mm Dia bolt Embed 1270 mm for 64 mm Dia bolt-

2B

away from traffic-